

Nureva™ HDL200 audio conferencing system

Ideal for small spaces

Trust the HDL200 system to deliver the best audio performance in your small meeting rooms. Seated, standing or walking around – no restrictions means your team can work the way that best suits them and their tasks while still being heard by remote participants. It installs in less than an hour in a variety of flexible configurations, for a clean uncluttered aesthetic. And its plug-and-play connectivity and continuous autocalibration ensure that setup is simple.

Thousands of virtual microphones

At the heart of the HDL200 audio conferencing system is Nureva's revolutionary Microphone Mist™ technology. It surpasses traditional audio conferencing technologies by filling a space with thousands of virtual microphones to provide true full-room pickup. For the first time, meeting participants can be heard no matter where they move in the room or which direction they face.

One simple solution

The HDL200 system was designed for simplicity. You can install it yourself in less than an hour. Plug-and-play connectivity to virtually all UC&C platforms means there are no drivers to install and the system autocalibrates, so no technician is needed for set up. The HDL200 can be installed in a variety of configurations, including on the wall (above or below a display), or even mounted to a mobile display stand.

Designed for smaller spaces today and tomorrow

The HDL200 also includes an integrated full-color display. Perfectly sized for smaller rooms, it displays useful information such as time, call status, volume, mute on/off, etc., to help keep conferences on track. With the launch of the Nureva API, the display will support further enhancements through future integrations with other products such as room control, building information management and room booking systems.

Easily manage and deploy multiple systems across the organization

Whether you are installing one system or hundreds, all HDL200 systems come with Nureva Console, a cloud-based platform that makes it easy to manage systems across multiple locations from a single, secure dashboard. Once enrolled, customers also receive an additional year of warranty, from two years to three, at no additional cost.



Designed for small spaces

Up to 18' by 18' (5.5 x 5.5 m)

4,096 virtual microphones

They fill the space providing full-room coverage

Advanced system processing capabilities

Simultaneously processes all 4,096 microphones with no latency due to scanning or refocusing on sounds

Compatible with UC&C platforms

Zoom, Microsoft® Teams, Skype® for Business, GoToMeeting®, Cisco WebEx™, StarLeaf and more

Continuous autocalibration

Adapts to room configurations dynamically

Plug and play

Recognized as a standard USB device. No drivers needed.

Advanced audio

Full duplex, acoustic echo cancellation, position-based gain control

Flexible installation

Above or below a display, on a wall (bracket included) or on a mobile stand (bracket optional)

Nureva Console

Manage products from anywhere. Automatic firmware updates. Additional year of warranty upon registration.

Integrated display

Full-color display for call status and optional additional third-party product integrations

GENERAL

Powerful system processors (15,000 MIPS)
 Continuous autocalibration
 Acoustic echo cancellation
 Position-based gain control
 Plug and play, no software or drivers required
 Integrated full-color display
 Compatible with leading UC&C platforms

MICROPHONES

| | |
|---------------------------------|------------------|
| Number | 10 |
| Type | Digital MEMS |
| Frequency response | 100Hz – 5 kHz |
| Total harmonic distortion (THD) | >0.25% (typical) |
| Transmission | Full duplex |

SPEAKERS

| | |
|------------------------------------|--------------------------|
| Number | 20W x2 |
| Type | 3.25" mid-woofer |
| Acoustic output (hardware capable) | 91 dB-SPL @ 1 m |
| Total harmonic distortion (THD) | 0.15% @ 1000Hz at 1 watt |
| Frequency response | 125-20,000Hz |
| Amplifier class | D |

CONNECTIONS

| | |
|-----------------------|-----------------------------|
| Interface to computer | USB type B 2.0 x1 |
| Power | Input jack for power supply |

OPERATING

| | |
|-------------------|--|
| Room size | Up to 18' x 18' (5.5 x 5.5 m) |
| Operating systems | Windows® 10, Windows 8, Windows 10, Mac® OS X® Mojave and Catalina |
| System setup | Plug and play |

PART NUMBERS

HDL200-B, HDL200 audio conferencing system, black bar
 HDL200-W, HDL200 audio conferencing system, white bar

OPTIONAL ACCESSORIES

CM-HDL200, camera mount HDL200
 DM-HDL200, display mount HDL200

SYSTEM INCLUDES

Integrated microphone and speaker bar
 Wall mounting bracket
 Power supply with country-specific power cable 6' (2 m), black
 USB type A-B cable, 15' (4.5 m) VW-1 rated, black
 Infrared remote
 Cable routing channel
 AAA batteries x2
 Documentation kit

POWER

| | |
|-------------------|---|
| Power rating | Universal switching 100-240V AC, 50-60Hz |
| Power consumption | <25W |

ENVIRONMENTAL

System temperature 0° C to 40° C (32° F to 104° F) operating temperature,
 -20° C to 70° C (-4° F to 158° F) storage temperature,
 humidity 5–90% (noncondensing)

WEIGHTS

| | |
|---------------------------------------|-------------------|
| Integrated microphone and speaker bar | 10.0 lb. (4.5 kg) |
| Shipping | 16.5 lb. (7.5 kg) |

DIMENSIONS

| | |
|---------------------------------------|---|
| Integrated microphone and speaker bar | Width: 46.4" (117.9 cm) Height: 4.8" (12.2 cm) Depth: 3.4" (8.6 cm) |
| Shipping | Width: 64.75" (164.4 cm) Height: 10.63" (27.0 cm) Depth: 9.5" (24.1 cm) |

CERTIFICATIONS

| | |
|-------------------------------|--|
| Electromagnetic compatibility | FCC Part 15, Class A ICES-003, Class A, CISPR 32 (EN55032), Class A CISPR 24 (EN55024), CISPR 35 (EN55035) |
| Safety | UL 62368, CAN/CSA-C22.2 NO. 62368, IEC/EN62368, AS/NZS 62368 |
| Environmental | RoHS, WEEE, REACH |

WARRANTY

Integrated microphone and speaker bar – Standard 2-year limited hardware (3 years with registration)
 Accessories and cables – 30 days

For more information

Nureva Inc.
 Tel. 403.699.9781
 sales@nureva.com
 enquiries@nureva.com